

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
20 October 2005 (20.10.2005)


PCT

(10) International Publication Number
WO 2005/098392 A1

- (51) International Patent Classification⁷: G01N 1/22
- (21) International Application Number:
PCT/IB2005/051145
- (22) International Filing Date: 7 April 2005 (07.04.2005)
- (25) Filing Language: Italian
- (26) Publication Language: English
- (30) Priority Data:
VC2004A000002 9 April 2004 (09.04.2004) IT
- (71) Applicant and
(72) Inventor: BRUZZI, Domenico [IT/IT]; Via Faldella 57, I-13044 Crescentino (Vercelli) (IT).
- (74) Agents: RONDANO, Davide et al.; Corso Emilia 8, I-10152 Torino (IT).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Declaration under Rule 4.17:
— of inventorship (Rule 4.17(iv)) for US only
- Published:
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PROBE AND SYSTEM FOR EXTRACTING GASES FROM A PROCESS ENVIRONMENT

WO 2005/098392 A1



(57) Abstract: A probe (S) for the extraction of gas from a process environment comprises a tubular element (2), which can be positioned within the process environment. This tubular element has at one end a gas aspiration opening (TS) and defines an internal cavity (CA) by which the interior of the process environment can be put into fluid communication with a gas take off system. The probe further includes a second tubular element (1) extending into the interior of the cavity of the first tubular element (2). This second tubular element has one end (UG) disposed at the aspiration opening end (that is to say the process environment side), formed in such a way as to inject the said accelerated gaseous fluid towards the aspiration opening of the first tubular element (2) and from there back to the process environment. Also envisaged is a system for the extraction of gas from a process environment which can be coupled to the probe, comprising a circuit (40, C) aspirating the gas from the process environment through the cavity (CA) of the first tubular element of the probe (2), and a circuit (50, C) for re-injecting the said gas into the same process environment through the second tubular element of the probe (1).